

BLACKFRIAR PAINTS LTD

TECHNICAL DATA SHEET

BF080 Blackfriar Wood Dye

Revision
date:
09/01/2007

<p><u>Product Information</u></p> <p><u>Description</u></p> <p>A high quality flat penetrating wood dye for new wood.</p> <p><u>Usage/purpose</u></p> <p>Furniture, floors, doors, wooden panelling, bar tops, joinery etc, inside and out. To colour wood prior to varnishing or French Polishing.</p> <p><u>Characteristics</u></p> <p>Deep penetrating.</p> <p><u>Finish</u></p> <p>Must be coated with a clear finish e.g. Varnish, Danish Oil, Wax Polish etc.</p> <p><u>Colour(s)</u></p> <p>Light Oak, Medium Oak, Dark Oak, Antique Pine Redwood (Mahogany) , Teak, Rosewood, Dark Jacobean, Chestnut.</p> <p><u>Packaging</u></p> <p>1l, 500ml, 250ml 125ml. Larger sizes may be available on request</p> <p><u>Disclaimer:</u></p> <p>The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p><u>Technical Spec</u></p> <p><u>Composition</u></p> <p>A blend of aliphatic/aromatic solvents, 'stained' with dyes</p> <p><u>Properties</u></p> <p>VOC Content: 568-653 g/litre.</p> <p><u>Performance</u></p> <p>Dependent on finish</p> <p><u>Surface Preparation</u></p> <p>Ensure the substrate to be treated is sound and free from any surface contaminant (e.g. wax, grease, polish etc).</p> <p><u>Application Method</u></p> <p>Brush, spray, lint free cloth. Ensure products are thoroughly shaken before use. Apply using brush, cloth or spray. If applying by brush apply one thin coat. Whilst the coat is wet remove surplus with a coarse cloth. A second application may be applied if there is still suction in the wood.</p> <p><u>Recommended Spreading Rate</u></p> <p>Up to 30m²/l depending on absorbency of the wood.</p> <p>For Technical Enquiries, Material Safety Data Sheets Telephone Sales on 0191 4106611</p>	<p><u>Thinning</u></p> <p>Not required</p> <p><u>Drying Time</u></p> <p>Touch dry in 1-3 hours. Re-coat time will depend on the absorbency of the wood and drying conditions. <u>Always</u> check on small area prior to coating the whole area.</p> <p><u>Cleaning</u></p> <p>Clean application equipment or spills with white spirit or Blackfriar Brush Cleaner.</p> <p><u>Limitations</u></p> <p>NB. For new wood only. <u>Not</u> recommended for use on previously coated surfaces even if stripped back to bare wood. If using a wax polish on top of Blackfriar Wood Dye, seal first with a coat of Blackfriar White French Polish.</p> <p><u>Environmental Info.</u></p> <p>Dangerous for the environment</p> <hr/> <p>Paint Product UN No. 1263</p> <hr/> <p>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</p>
---	--	---